



Timken BEARINGS ITALIA S.P.A.



7212 BECBP Bearing 2D drawings and 3D CAD models

60 mm x 110 mm x 22 mm SKF 7212 BECBP Angular Contact Ball Bearings

Bearing No. 7212 BECBP

Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.78
EAN	7316577292209
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 3 ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Polymer
Contact Angle	40 Degree
Internal Clearance	CB
Number of Bearings	1 (Single)
Mounting Arrangement	Universal
Inch - Metric	Metric
Long Description	60MM Bore; 110MM Outside Diameter; 22MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3 ISO P6; No Filling Slot; No Snap



Timken BEARINGS ITALIA S.P.A.

	Ring
Other Features	Normal Axial Internal Clearance
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	7212 BECBP
Weight / LBS	1.713
B	0.866 Inch 22 Millimeter
D	4.331 Inch 110 Millimeter
d	2.362 Inch 60 Millimeter
bore diameter:	60 mm
radial static load capacity:	50 kN
outside diameter:	110 mm
cage material:	Nylon
overall width:	22 mm
outer ring width:	22 mm
contact angle:	40 °
maximum rpm:	7500 RPM
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	Not Rated
closure type:	Open
fillet radius:	1.5 mm
radial dynamic load capacity:	61 kN
series:	72
d	60 mm



Timken BEARINGS ITALIA S.P.A.

D	110 mm
B	22 mm
d ₁	79.6 mm
d ₂	69.32 mm
D ₁	91.55 mm
a	47 mm
r _{1,2} min.	1.5 mm
r _{3,4} min.	1 mm
d _a min.	69 mm
D _a max.	101 mm
D _b max.	104 mm
r _a max.	1.5 mm
r _b max.	1 mm
Basic dynamic load rating C	61 kN
Basic static load rating C ₀	50 kN
Fatigue load limit P _u	2.12 kN
Reference speed	7000 r/min
Limiting speed	7500 r/min
Calculation factor A	0.0344
Calculation factor k _r	0.095
Calculation factor e	1.14
Calculation factor X	0.35
Calculation factor Y ₀	0.26
Calculation factor Y ₂	0.57
Calculation factor X	0.57
Calculation factor Y ₀	0.52
Calculation factor Y ₁	0.55
Calculation factor Y ₂	0.93
Mass bearing	0.8 kg